

LIGHTING KEYNOTES **GENERAL CEILING PLAN NOTES** (NOT ALL USED EVERY FLOOR)

DO NOT SCALE DRAWINGS. LK 1. DECORATIVE LIGHTING: REFER TO LIGHTING SCHEDULE

OR ELEVATIONS FOR MOUNTING HEIGHTS.

. GYP. BD. CEILINGS AND THEIR ASSOCIATED BULKHEADS ARE TO BE PAINTED P-33A UNLESS NOTED OTHERWISE. UNLIKE FLOOR PLAN DIMENSIONS, THOSE SHOWN ON THE REFLECTED CEILING PLAN ARE FINISHED

DIMENSIONS UNLESS NOTED OTHERWISE.

- CEILING ELEVATIONS ARE TO THE FINISHED FACE OF THE CEILING FINISH MATERIAL.
- BULKHEAD DIMENSIONS ARE TO THE FINISHED FACE OF GYP. BD.
- DIMENSIONS TO LIGHT FIXTURES ARE TO THE CENTERPOINT OF THE FIXTURE, THE FINISHED EDGE OF FIXTURE, OR TO THE CENTERLINE OF ASSOCIATED CEILING GRID SYSTEM.
- LETTER DESIGNATIONS WITHIN A DIMENSION STRING (SUCH AS "A", "B", "C" AND SO ON) INDICATE THAT THE DIMENSION IS TO BE FIELD DETERMINED AND IT IS TO BE EQUAL TO OTHER DIMENSIONS OF THE SAME LETTER THROUGHOUT THAT SPECIFIC DRAWING SHEET, BUT NOT TO THE SAME DESIGNATION ON OTHER DRAWING
- USE OF "EQUAL" OR "EQ" WITHIN A DIMENSION STRING INDICATES A DIMENSION THAT IS TO BE EQUAL ONLY RELATIVE TO OTHER EQUAL CALLOUTS ON THE SAME DIMENSION STRING IN WHICH IT APPEARS. DIMENSIONS CALLED OUT AS EQUAL ON TWO DIFFERENT DIMENSION STRINGS ARE NOT NECESSARILY EQUAL TO EACH
- ALL DESIGN TEAM DRAWINGS SHALL BE USED TO LOCATE BUILDING ELEMENTS. CONTACT THE ARCHITECT WITH CONFLICTS, DISCREPANCIES, AND OMISSIONS PRIOR TO COMMENCEMENT OF WORK. WRITTEN DOCUMENTATION SHALL BE PROVIDED BY THE CONTRACTOR REGARDING
- STRUCTURAL, MECHANICAL, ELECTRICAL, PLUMBING, LOW VOLTAGE AND FOOD SERVICE ELEMENTS ARE SHOWN FOR REFERENCE ONLY. VERIFY EACH ELEMENT WITH THE ASSOCIATED ENGINEER'S DRAWINGS. COORDINATE CONFLICTS WITH THE ARCHITECT.
- REFER TO SPECIFICATIONS FOR EACH ITEM REPRESENTED WITHIN THE DRAWING SET.
- . GENERAL CONTRACTOR TO PROVIDE BACKER ROD AND SEALANT, OF A TYPE APPROPRIATE TO EACH CONDITION, BETWEEN MATERIALS BOTH SIMILAR AND DISSIMILAR THROUGHOUT THE INTERIOR AND EXTERIOR OF THE BUILDING. (COLORS TO BE SELECTED BY ARCHITECT)
- 0. NOT ALL LIGHT FIXTURES ARE REPRESENTED ON THE ARCHITECTURAL DRAWINGS. SEE ELECTRICAL DRAWINGS FOR ADDITIONAL LIGHT FIXTURE TYPES AND LOCATIONS. CONFIRM ANY DISCREPANCIES BETWEEN DRAWINGS WITH THE ARCHITECT PRIOR TO COMMENCEMENT OF WORK.
- I. WHERE GYP. BD. CEILINGS ARE INDICATED TO BE LOWER THAN ADJACENT ACT CEILINGS THE CONTRACTOR IS TO PROVIDE A FINISHED VERTICAL GYP. BD. BULKHEAD RETURN FROM THE LOWER FINISHED GYP. BD. CEILING TO A MINIMUM OF 6" ABOVE THE ADJACENT ACT CEILING UNLESS NOTED OTHERWISE. SEE FLOOR PLANS AND LIFE SAFETY PLANS.
- 2. WHERE GYP. BD. CEILINGS ARE INDICATED TO BE LOWER THAN ADJACENT GYP. DB. CEILINGS THE CONTRACTOR IS TO PROVIDE A CONTINUOUS FINISHED VERTICAL GYP. BD. BULKHEAD RETURN TO THE ADJACENT FINISHED GYP.
- 13. EACH STAIR ENCLOSURE SHAFT IS TO HAVE A 1-HR RATED ROOF-CEILING ASSEMBLY OF 5/8" GYP. BD. ON RESILIENT CHANNELS ATTACHED TO THE UNDERSIDE OF THE ROOF STRUCTURE.
- 14. EACH FIRE RATED BUILDING SHAFT IS TO HAVE A CLOSURE AT THE TOP AND BOTTOM OF THE SHAFT THAT MATCHES THE FIRE RATING OF THE SHAFT.
- 15. ACCESS PANELS AND / OR ACCESS POINTS TO BE REQUIRED. COORDINATE LOCATIONS WITH MEP DRAWINGS AND CONFIRM WITH ARCHITECT PRIOR TO FINALIZING LAYOUT. ACCESS POINTS TO BE LOCATED
- LIGHT SHOULD BE CENTERED WITHIN THE GRID/PATTERN.
- 17. UNLESS OTHERWISE INDICATED, LOCATE FIXTURES CENTERED IN ROOM OR SPACE W/ EQUAL SPACING BETWEEN FIXTURES (WHERE OCCURS) AND TYPICAL SPACING BETWEEN FIXTURES AND PERIMETER WALLS, BEAMS, CEILING ELEMENTS OR OTHER ARCHITECTURAL FEATURES; CONFIRM WITH ARCHITECT PRIOR TO FINALIZING LAYOUT.
- 18. PROVIDE 4" SOUND ATTENUATION BLANKET ABOVE ALL

CODED CEILING NOTES

1.2 BEAMS TO BE EXPOSED STEEL AND PAINTED P-20

ALIGN CONDUIT BETWEEN FIXTURES, TYP. MAINTAIN OPENING IN CEILING FOR ROOF

BEAMS TO BE EXPOSED STEEL AND PAINTED P-18

PAINT EXISTING BEAMS WHERE EXPOSED; P-33A

1.1 PAINT EXTERIOR SOFFIT; P-33A

browning

626 North Illinois Street Indianapolis, Indiana 46204 Phone: (317) 635-5030 Website: www.browningday.com

CRDV Findlay Market LLC

1733 W Lane Avenue Columbus, Ohio 43221 (513) 559-0048 https://www.cohatch.com

The Model Group

Contractor

1826 Race Street Cincinnati, Ohio 45202 (513) 559-0048 https://modelgroup.net

The Kleingers Group Civil Engineer

6219 Centre Park Drive West Chester Township, Ohio 45069 Phone: (513) 779-7851 Website: https://www.kleingers.com

Lawson Elser Engr Structural Engineer

650 E. Carmel Dr., Suite 150 Carmel, IN 46032 Phone: (317) 574-9409x2 Website: www.lawsonelser.com

Gooderum & Assoc. MEP Engineer 874 Cheltenham Way

Phone: (317) 506-8151

Brightstone Creative Tenant Designer

25 North Street

COhatch Tenant

Dublin, Ohio 43017 Phone: (614) 578-0249

1733 W Lane Avenue Columbus, Ohio 43221

https://www.cohatch.com

(513) 559-0048

Avon, IN 46123

LOCATED NEAR CLEANOUTS, DUCT DAMPERS, ETC. AS WITHIN LIMITS OF ACCOUSTICAL CEILING GRID WHERE

16. WHERE RECESSED DOWNLIGHTS ARE LOCATED WITHIN A CEILING TILE OR DECORATIVE PATTERNED CEILING, THE

exp: 12-31-2023

Construction Documents

COhatch - Leader Building

132 W Elder St, Cincinnati,

CERTIFICATION

Ohio, 45202

Drawn By: Author

Checked By: Checker

Scale: See Drawing

Issue Date: November 18, 2022

HATCH/LADDER ACCESS. 3.1 AC-45; MOUNTING HEIGHTS PER FINISH SCHEDULE 4.2 CUSTOM DECORATIVE CEILING FRAME - TYPE A; REF. DETAIL FOR FINISHES 4.3 CUSTOM DECORATIVE CEILING FRAME - TYPE B; REF.

DETAIL FOR FINISHES T.1 EXISTING DECORATIVE CEILING TO REMAIN; CLEAN AND PREP FOR NEW PAINT; P-33A TYP; PATCH AND REPAIR AS NEC.; EXTENTS SHOWN AS REF. ONLY - FIELD VERIFY EXISTING CONDITIONS AND ADJUST LIGHTING/MEP LAYOUT AS NEC.

PAINTED GYP. HARDLID CEILING; P-33A T.3 FUR EXISTING PLASTER CEILING TO CONCEAL ELECTRICAL CONDUIT. PAINT P-33A. T.4 PAINTED GYP. HARDLID CEILING; P-54

T.5 EXISTING STAIR TO BE REMOVED COMPLETE. CEILING TO BE LEFT AS EXPOSED UNDERSIDE OF NEW FLOOR T.6 PAINTED GYP. HARDLID CEILING & BULKHEADS; P-4

T.7 EXISTING PLASTER CEILING. PAINT P-33A TYP. T.8 EXISTING EXPOSED STRUCTURE TO REMAIN; CLEAN AND PREP FOR NEW PAINT; P-33A TYP. T.10 EXISTING EXPOSED STRUCTURE TO REMAIN, INSTALL KRAFT-FACED R-38 BATT INSULATION BETWEEN JOISTS

T.11 PAINTED GYP. HARDLID CEILING; P-33A. INSTALL THIS AREA. T.12 EXISTING EXPOSED STRUCTURE TO REMAIN; 2-HR ASSEMBLY TO BE INSTALLED THIS AREA. SEE A0.11 FOR MORE INFORMATION.

SYMBOL LEGEND

CODED NOTES OF VARYING TYPES: SEE SCHEDULES ON THIS

MATERIAL FINISH NOTE. SEE A5-SERIES OF DRAWINGS AND SPECIFICATIONS

1-HR RATED ASSM, SEE PLANS, WALL TYPES & SECTIONS

2-HR RATED ASSM, SEE PLANS, WALL TYPES & SECTIONS 3-HR RATED ASSM, SEE PLANS, WALL TYPES & SECTIONS 4-HR RATED ASSM, SEE PLANS, WALL TYPES & SECTIONS

Revision Description For Construction 05-13-2022 ADD #3 05-23-2022 REV #1 11-18-2022 12 ADD #10 03-15-2023

REVISION SCHEDULE

Basement, RCP Plan

A1.00-C1