



# GENERAL CEILING PLAN NOTES

1. DO NOT SCALE DRAWINGS.
2. GYP. BD. CEILINGS AND THEIR ASSOCIATED BULKHEADS ARE TO BE PAINTED **P-33A** UNLESS NOTED OTHERWISE.
3. UNLIKE FLOOR PLAN DIMENSIONS, THOSE SHOWN ON THE REFLECTED CEILING PLAN ARE FINISHED DIMENSIONS UNLESS NOTED OTHERWISE.

CEILING ELEVATIONS ARE TO THE FINISHED FACE OF THE CEILING FINISH MATERIAL.






BULKHEAD DIMENSIONS ARE TO THE FINISHED FACE OF GYP. BD.

DIMENSIONS TO LIGHT FIXTURES ARE TO THE CENTERPOINT OF THE FIXTURE, THE FINISHED EDGE OF THE FIXTURE, OR TO THE CENTERLINE OF ASSOCIATED CEILING GRID SYSTEM.
4. LETTER DESIGNATIONS WITHIN A DIMENSION STRING (SUCH AS "A", "B", "C" AND SO ON) INDICATE THAT THE DIMENSION IS TO BE FIELD TO FIELD, AND IT IS TO BE EQUAL TO OTHER DIMENSIONS OF THE SAME LETTER THROUGHOUT THAT SPECIFIC DRAWING SHEET, BUT NOT TO THE SAME DESIGNATION ON OTHER DRAWING SHEETS.
5. USE OF "EQUAL" OR "EQ" WITHIN A DIMENSION STRING INDICATES A DIMENSION THAT IS TO BE EQUAL ONLY RELATIVE TO OTHER EQUAL CALLOUTS ON THE SAME DRAWING. A DIMENSION STRING WHICH APPEARS, DIMENSIONS CALLED OUT AS EQUAL ON TWO DIFFERENT DIMENSION STRINGS ARE NOT NECESSARILY EQUAL TO EACH OTHER.
6. ALL DESIGN TEAM DRAWINGS SHALL BE USED TO LOCATE BUILDING ELEMENTS. CONTACT THE ARCHITECT WITH CONFLICTS, DISCREPANCIES, AND OMISSIONS PRIOR TO COMMENCEMENT OF WORK. THE ARCHITECT'S RESPONSE SHALL BE PROVIDED BY THE CONTRACTOR REGARDING SUCH ITEMS.
7. STRUCTURAL, MECHANICAL, ELECTRICAL, PLUMBING, LOW VOLTAGE AND FOOD SERVICE ELEMENTS ARE REFERRED TO ONLY WHEN THEY APPEAR WITHIN THE DRAWING WITH THE ASSOCIATED ENGINEER'S DRAWINGS. COORDINATE CONFLICTS WITH THE ARCHITECT.
8. REFER TO SPECIFICATIONS FOR EACH ITEM REPRESENTED WITHIN THE DRAWING SET.
9. GENERAL CONTRACTOR TO PROVIDE BACKER ROD AND SEALANT, OF A TYPE AND QUALITY AS REQUIRED BY CONDITION. BACKER MATERIALS BOTH SIMILAR AND DISSIMILAR LOCATED BETWEEN THE INTERIOR AND EXTERIOR OF THE BUILDING. (COLORS TO BE SELECTED BY ARCHITECT)
10. NOT ALL LIGHT FIXTURES ARE REPRESENTED ON THE ARCHITECT'S DRAWINGS. SEE ELECTRICAL DRAWINGS FOR ADDITIONAL LIGHT FIXTURE TYPES AND LOCATIONS. CONFIRM ANY DISCREPANCIES BETWEEN DIMENSIONS WITH THE ARCHITECT PRIOR TO COMMENCEMENT OF WORK.
11. WHERE GYP. BD. CEILINGS ARE INDICATED TO BE LOWER THAN ADJACENT ACCT CEILINGS THE CONTRACTOR IS TO PROVIDE A FINISHED VERTICAL GYP. BD. BULKHEAD RETURN FROM THE LOWER CEILING TO THE ADJACENT BD. CEILING TO A MINIMUM OF 6" ABOVE THE ADJACENT ACCT CEILING UNLESS NOTED OTHERWISE. SEE FLOOR PLANS AND LIFE SAFETY PLAN.
12. WHERE GYP. BD. CEILINGS ARE INDICATED TO BE LOWER THAN ADJACENT GYP. DB. CEILINGS THE CONTRACTOR IS TO PROVIDE A CONTINUOUS FINISHED VERTICAL GYP. BD. BULKHEAD RETURN TO THE ADJACENT FINISHED GYP. BD. BD. CEILING.
13. EACH STAIR ENCLOSURE SHAFT IS TO HAVE A 1-HR RATED ROOF-CEILING ASSEMBLY OF 5/8" GYP. BD. ON RESILIENT CHANNELS ATTACHED TO THE UNDERSIDE OF THE ROOF STRUCTURE.
14. EACH RATED BUILDING SHAFT IS TO HAVE A CURB AND THE TOP AND BOTTOM OF THE SHAFT THAT MATCHES THE FIRE RATING OF THE SHAFT.
15. ACCESS PANELS AND / OR ACCESS POINTS TO BE LOCATED NEAR CLEANOUTS, DUCT DAMPERS, ETC. AS REQUIRED. RECORDED THE LOCATIONS WITHIN THE DRAWINGS AND CONFIRM WITH ARCHITECT PRIOR TO FINALIZING LAAYOUT. ACCESS POINTS TO BE LOCATED WHERE LOCATIONS OF ACOUSTICAL CEILING GRID WHERE POSSIBLE.
16. WHERE RECESSED DOWNLIGHTS ARE LOCATED WITHIN A CEILING TILE OR DECORATIVE PATTERNED CEILING, THE LIGHT SHOULD BE CENTERED WITHIN THE GRID/PAVING.
17. UNLESS OTHERWISE INDICATED, LIGHT FIXTURES ARE TO BE SPACED IN ROOM OR HALLS TO PROVIDE EQUAL SPACING BETWEEN FIXTURES (WHERE OCCURS) AND TYPICAL SPACING BETWEEN FIXTURES AND PERIMETER WALLS. BULKHEAD LIGHTING ELEMENTS AND OTHER ARCHITECTURAL FEATURES, CONFIRM WITH ARCHITECT PRIOR TO FINALIZING LAAYOUT.
18. PROVIDE 4" SOUND ATTENUATION BLANKET ABOVE ALL OFFICES.

## SYMBOL LEGEND

<div style="border: 1px solid black; padding: 5px; display: inline-block;"> T.3 CEL </div>	<p>CODED NOTES OF VARYING TYPES; SEE SCHEDULES ON THIS SHEET</p>
	<p>MATERIAL FINISH NOTE. SEE A5-SERIES OF DRAWINGS AND SPECIFICATIONS</p>

1-HR RATED ASSM.	
2-HR RATED ASSM.	
3-HR RATED ASSM.	
4-HR RATED ASSM.	
5-HR RATED ASSM.	

---



## Construction Documents

COhatch - Leader Building

132 W Elder St, Cincinnati,  
Ohio, 45202

Project No.: 21023.A  
 Drawn By: Author  
 Checked By: Checker  
 Scale: See Drawing  
 Issue Date: November 18, 2022

REVISION SCHEDULE		
Rev. #	Revision Description	Issue Date
4	ADD #3	05-23-2022
5	ADD #4	06-20-2022
8	REV #1	11-18-2022
9	ADD #7	12-07-2022

4th Floor RCP Plan

**A1.04-C1**